



**UNI EN 13241-1
(UE) N. 305/2011**

Material

S235JR UNI EN 10025:05 steel
AISI 304L stainless steel (by request)

Treatment

hot galvanising UNI EN ISO 1461:09 polyester powder coating over galvanising

Fixings

standard M8x25 stainless steel bolt
anti-theft M8x25 stainless steel bolt

***GATES TO SIZE, WITH CERTIFICATION, BY REQUEST**

STANDARD SUPPLY

- n° 1 tubular frame with double fixed handle
- n° 2 front stanchions
- n° 2 rear stanchions
- n° 1 sliding guide to be built in
- n° 2 wheels with pin
- n° 2 guide olives with pins
- n° 1 rear stop
- lock with fold-away hook
- Bottom rail with band
- Mirror as chosen

ACCESSORIES BY REQUEST

- stanchion cover with hole for flashing light
- galvanised iron corrugated mesh
- mesh 15x15 with frame (installation using clips, by the client)
- lock with fold-away
- hook and handle
- sliding guide to be anchor bolted)
- bottom rail with 2/3 bands or in diamond pointed plating

STANDARD DIMENSIONS*

Opening (L)	Height (H)	Stanchions
mm	mm	mm
Min 2000	Min 1000	Min 100 x 100
q	q	q
Max 8130	Max 2500	Max 200 x 200